

## Unitemp Stock List December 2023

Model	Options	Serial No	PO Number
ARG-0680-5-E	400V AC, 3 phase, 50Hz, CE, R449A + R508A, VW with ceiling light, Time signal terminals 8 contacts(English), Overcool protector, Standard CP removal right, Additional CP 100mm Position F2, Additional CP 150mm Position F3, CP rubber plug with slits 150mm x 2, CP rubber plug with slits 100mm x 2, Shelf & brackets x 3	4140000135	EEG-4341-01-01-B
ARL-1100-AE	400 V AC, 3 phase, 50 Hz, CE marking, R449A, Viewing window, Additional automatic drain function		EEG-4860-01-01
ARL-0680-AE	400V, 3 phase, 50 Hz, CE, NR R449A, Viewing window with ceiling light, Activation of Temperature change rate input and Multi step setting	4120520618	EEG-4483-01-01
ARS-0390-AE	400V, 3 phase, 50 Hz, CE, NR R449A, Viewing window with ceiling light, Additional automatic drain function (software update)		EEG-4915-01-01
ARS-0680-5-E	400V, 3 phase, 50 Hz, CE;, NR R449A + R508A, Shelf & shelf brackets, Door with viewing window, continuous water supply with pressure-reducing valve, Specimen temperature control, non-insulated type, Activation of Temperature change rate input and Multi step setting	4140000237	EEG-4485-01-02
ARS-0680-5-E	400V, 3 phase, 50 Hz, CE;, NR R449A + R508A, Shelf & shelf brackets, Door with viewing window, continuous water supply with pressure-reducing valve, Specimen temperature control, non-insulated type, Activation of Temperature change rate input and Multi step setting	4140000234	EEG-4490-01-02
ARS-0680-5-E	400V AC, 3 phase, 50Hz, CE, R449A + R508A, VW with ceiling light, Shelf & brackets x 2, Overcool protector, Time signal terminals 8 contacts (English), Continuous water supply with pressure-reducing valve, Standard CP removal right, Additional CP 100mm Position F1, Additional CP 150mm Position F2 & F3, CP rubber plug with slits 150mm x 2, CP rubber plug with slits 100mm x 2. Factory acceptance test (IEC60068-2-30. IEC60068-	4140000136	EEG-4341-02-01
ARS-0680-5-E	400V AC, 3 phase, 50Hz, CE, R449A + R508A, VW with ceiling light, Shelf & brackets x 2, Overcool protector, Time signal terminals 8 contacts (English), Continuous water supply with pressure-reducing valve, Standard CP removal right, Additional CP 100mm Position F1, Additional CP 150mm Position E2 & F3, CP rubber plug with slits 150mm x 2. CP rubber plug with slits 100mm	4140000138	EEG-4341-03-01
ARS-0680-AE	400V, 3 phase, 50 Hz, CE, NR R449A, Viewing window with ceiling light, Activation of Temperature change rate input and Multi step setting, Additional automatic drain function (software update)	4120520620	EEG-4514-01-01

ARS-0680-AE	400V, 3 phase, 50 Hz, CE, NR R449A, Viewing window with ceiling light, Additional automatic drain function (software update)	4120520682	EEG-4766-01-01
ARS-1100-10-E	Voltage 380 V AC, 3 phase, 50 Hz, CE marking, R449A+R508A, Additional cable port 100mm on Pos 2F, Continuous water supply with pressure reducing valve, Viewing window with ceiling light, Floor reinforcement with body reinforcement 300kg, Specimen temperature control Insurated type. RS-		EEG-4636-02-04
ARS-1100-10-E	Voltage 380 V AC, 3 phase, 50 Hz, CE marking, R449A+R508A, Additional cable port 100mm on Pos 2F, Continuous water supply with pressure reducing valve, Viewing window with ceiling light, Floor reinforcement with body reinforcement 300kg, Specimen temperature control Insurated type. RS-		EEG-4636-03-04
ARS-1100-10-E	Voltage 380 V AC, 3 phase, 50 Hz, CE marking, R449A+R508A, Additional cable port 100mm on Pos 2F, Continuous water supply with pressure reducing valve, Viewing window with ceiling light, Floor reinforcement with body reinforcement 300kg, Specimen temperature control Insurated type. RS-		EEG-4636-06-03
ARS-1100-5-E	400 V AC, 3 phase, 50 Hz, CE NR R449A + R508A, Viewing window, 1 shelf with brackets, continuous water supply with pressure-reducing valve, Specimen temperature control (non-insulated type), Multi step	4140000210	EEG-3995-01-03
ARS-1100-5-E	400 V AC, 3 phase, 50 Hz, CE NR R449A + R508A Viewing window, 1 shelf with brackets, continuous water supply with pressure-reducing valve, Specimen temperature control (non-insulated type), Multistep	4140000223	EEG-4053-01-03
ARS-1100-AE	400 V AC, 3 phase, 50 Hz, CE marking, R449A, Viewing window, Additional automatic drain function		EEG-4902-01-01
ARS-1430-15	Refrigerant R449A + R508A, CE marking, Inspection report, General export specification / export packing fee / language (English), Floor reinforcement up to 300 kg, shelf with shelf brackets, Specimen temperature control (non-insulated type), Activation of Temperature change rate input and Multi step	3292003616	EEG-4457-01-01
LHU-114	230 V AC, 1 ph, 50Hz, CE; Inner door		EEG-4977-01-01
LU-114	230 V AC, 1 ph, 50, CE	1013005497	EEG-4804
PL-3J	400 V AC, 3 ph, 50 Hz, CE; R449A, 180°C spec , 1 shelf with brackets, standard cable port-less, additional 100mm cable port left side on std cable position		EEG-4948-01-01
SH-262	Voltage 230 V AC, 1 phase, 50 Hz, CE, NR R449A, Power plug C type, viewing window, Additional automatic drain function (software update)		EEG-4939-01-01
SH-642	Voltage 230 V AC, 1 phase, 50 Hz, CE, NR R449A, Power plug C type, viewing window, Additional automatic drain function (software update)		EEG-4865-01-01

SH-662	230 V AC, 1 ph, 50, CE; viewing window, 180°C spec, Power cable incl. plug C type, R449A, Additional automatic drain function (software update)		EEG-4873-01-01
TSA-103ES-W	400 V, 3 phase, 50 Hz, CE, R449A, flat cable port 65 x 125 with plug in hardness 15, casters, product /specimen temp monitor with trigger function; defrost	155003220	EEG-4540-01-01
TSA-203ES-W	AC400V AC 3ph, 50Hz, CE R449A, Silicone plugs in hardness 15 for the flat cable port 65mm x 125mm, casters, Product/Specimen temperature monitor with trigger function, Flat cable port 65x125mm x2, Floor reinforcement 200kg, Defrost-free operation, Remove standart cable port Ø 50mm left with plug		EEG-4947-01-01
TSA-303EL-W	400V, 3 phase, 50 Hz, CE, Silicone plugs in hardness 15 for the flat cable port 65mm x 125mm, casters, Product/specimen temperature monitor with trigger function, Standard cable port removal 50mm, Flat cable port 65mm x 125mm x2, Floor reinforcement 200kg, Defrost free operation, Ambient temperature exposure, Additional Hot Zone Heater, Additional cold zone accumulator (in total 3 pcs). Additional exhaust	155003201	EEG-4506-01-01
TSD-101-W	400V, 3 phase, 50 Hz, CE, NR R449A, Casters with leveling feet, Viewing window	141000564	EEG-4644-01-01
TSE-12-A	400V, 3 phase, 50 Hz, CE, R449A		EEG-4864-01-01